

CLAIMS

1. An object-oriented method for transferring a file system including folders and data files from a source data storage controlled by a source data processing unit to a destination data storage controlled by a destination data processing unit over a transfer medium, said method comprising the steps of:

building in said source data storage at least one file object containing a data package to be transferred;

generating a descriptor file including parameters associated with said file object;

generating an archive file including said data package; and

transmitting said descriptor file and said archive file from said source data processing unit to said destination data processing unit over said transfer medium.

2. An object-oriented method according to claim 1, wherein said file object is built by using a file transfer tool model including:

a header containing the following functions: set directory name, get environment, set environment, create, and install data; and

a body containing the following items: directory name, installed directory, size, version, and data package.

3. An object-oriented method according to claim 1, wherein said file object is a component object corresponding to files which are associated with a directory.

4. An object-oriented method according to claim 1, wherein said file object is an object corresponding to files which are associated with a root directory.

5. An object-oriented method according to claim 1, wherein the steps of generating said descriptor file and generating said archive file comprise the steps of:

defining the descriptor file in said source data storage;

setting a directory name in said descriptor file;

creating said archive file from the data package; and
setting remaining parameters in said descriptor file.

6. An object-oriented method according to claim 5, wherein said remaining parameters comprise installed directory, size, and version.

5 7. An object-oriented method according to claim 1, further comprising the steps of:
reading a received descriptor file;
defining a file object from information contained in said descriptor file;
setting an environment parameter of said file object with a value got from said descriptor
file; and
unarchiving data contained in the received archive file and installing said data in said
destination data storage.

8. An object-oriented method for receiving in a destination storage controlled by a destination
data processing unit a file system which is transferred from a source data storage controlled by a
source data processing unit, comprising the steps of:
reading a received descriptor file;
defining a file object from information contained in said descriptor file;
setting an environment parameter of said file object with a value got from said descriptor
file; and
unarchiving data contained in the received archive file and installing said data in said
20 destination data storage.

9. An object-oriented system for transferring a file system including folders and data files from
a source data storage controlled by a source data processing unit to a destination data storage
controlled by a destination data processing unit over a transfer medium, said system comprising:
means for building in said source data storage at least one file object containing a data
25 package to be transferred;
means for generating a descriptor file including parameters associated with said file object;

means for generating an archive file including said data package; and
means for transmitting said descriptor file and said archive file from said source data processing unit to said destination data processing unit over said transfer medium.

10. An object-oriented system according to claim 9, further comprising:

5 means for reading a received descriptor file;
means for defining a file object from information contained in said descriptor file;
means for setting an environment parameter of said file object with a value got from said descriptor file; and
means for unarchiving data contained in the received archive file and installing said data in said destination data storage.

11. An object-oriented system for receiving in a destination storage controlled by a destination data processing unit a file system which is transferred from a source data storage controlled by a source data processing unit, comprising:

10 means for reading a received descriptor file;
means for defining a file object from information contained in said descriptor file;
means for setting an environment parameter of said file object with a value got from said descriptor file; and
means for unarchiving data contained in the received archive file and installing said data in said destination data storage.

20 12. A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform object-oriented method steps for transferring a file system including folders and data files from a source data storage controlled by a source data processing unit to a destination data storage controlled by a destination data processing unit over a transfer medium, said method steps comprising

25 building in said source data storage at least one file object containing a data package to be transferred;
generating a descriptor file including parameters associated with said file object;

generating an archive file including said data package; and
transmitting said descriptor file and said archive file from said source data processing unit
to said destination data processing unit over said transfer medium.

13. A program storage device to claim 12, said method steps further comprising:
5 reading a received descriptor file;
defining a file object from information contained in said descriptor file;
setting an environment parameter of said file object with a value got from said descriptor
file; and

unarchiving data contained in the received archive file and installing said data in said
destination data storage.

14. A program storage device readable by a machine, tangibly embodying a program of
instructions executable by the machine to perform object-oriented method steps for receiving in a
destination storage controlled by a destination data processing unit a file system which is
transferred from a source data storage controlled by a source data processing unit, said method
steps comprising

reading a received descriptor file;
defining a file object from information contained in said descriptor file;
setting an environment parameter of said file object with a value got from said descriptor
file; and

20 unarchiving data contained in the received archive file and installing said data in said
destination data storage.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100